POLY-CRETE® SLB

DUR-A-FLEX®
INNOVATION FROM THE FLOOR UP

SYSTEM OVERVIEW

POLY-CRETE SLB is a 100% solids, seamless 3/16" cementitious-urethane self-leveling flooring system with a flintshot quartz aggregate broadcast, providing a slip-resistant finish. The body coat is resistant to thermal shock and is moisture mitigating which can eliminate the use of a primer in most environments, while topcoat options offer a wide selection of chemical and abrasion resistant finishes.

FEATURES & BENEFITS

• **Self Leveling**
A uniform, more even floor system

• **Moisture Mitigating**
Installs in more environments, including those with high moisture levels up to 99% RH

• **Non Slip**
Texture from the aggregate broadcast aids in a safer floor, even when wet

• **Thermal Shock Resistant**
Usable in harsh environments with high thermal cycling or rapid changes in temperature

COMMON USE SITES

- Kitchens
- Warehouses
- High Traffic Areas
- Storage
- Light Manufacturing
- Food Processing
- Breweries/Distilleries

MADE WITHOUT RED LIST MATERIALS
ZERO VOC
mindful MATERIALS
U.S. GREEN BUILDING COUNCIL MEMBER

COLORS

Available in standard solid color topcoats. For a full list of available colors visit **DUR-A-FLEX.COM**

BLUE*

GREY

CHARCOAL

RED

DARK GREY

GREEN*

CHESTNUT

Poly-Crete MD, MDB, SLB, HF systems and Poly-Crete TF Plus topcoat feature a matte finish. For UV stability use with one of these topcoats: Accelera, Shop Floor, Armor Top, and Color-Fast.
*Poly-Crete Color-Fast in these colors require a grout coat of Poly-Crete TF Plus to ensure consistent color.

IMPORTANT!

Before using DUR-A-FLEX products, read and understand its accompanying Safety Data Sheet & Application Instructions for important safety information.

STANDARD TERMS AND CONDITIONS OF SALE, INCLUDING STANDARD WARRANTY APPLY - VISIT **DUR-A-FLEX.COM** FOR THE LATEST VERSION

v1

DUR-A-FLEX
INNOVATION FROM THE FLOOR UP

CONNECTICUT | GEORGIA | ILLINOIS | CALIFORNIA
TOLL FREE 800-253-3539 | 860-528-9838 | DUR-A-FLEX.COM