

SURE-STEP™
Slip-Resistant Additive

DESCRIPTION

SURE-STEP slip-resistant additive is a finely ground polymer material for addition to concrete sealers for slip resistance. This additive can be added to most film-forming water- and solvent-based sealers, including the CS-309™, DECRA-SEAL™, VOCOMP®, TIAH®, and SEAL CURE™ products from W. R. MEADOWS. Please consult sealer manufacturer prior to using if using a product not listed above.

SURE-STEP provides improved abrasion resistance and is more comfortable to bare feet on treated surfaces than sand or aggregate additives. The product's low density and insolubility characteristics will help reduce settling and provide optimum performance in its various applications without changing the viscosity. Due to its low density, SURE-STEP stays suspended in thin materials.

USES

SURE-STEP is perfect for use on areas where a slip-resistant surface is desired. This includes walkways, driveways, garage floors, patios, and other surfaces.

FEATURES/BENEFITS

- Provides improved abrasion resistance.
- Does not change viscosity.
- Allows easy cleaning of the surface.
- Provides slip-resistance properties on surface without sacrificing comfort for barefoot traffic.

PACKAGING

16 Oz. Units (12/carton)

COVERAGE

The 16 oz. (473 mL) container is recommended for five-gallon (18.9 L) pails.

SHELF LIFE

When stored indoors in original, unopened containers at temperatures between 40° - 90° F (4° - 32° C), optimum performance and best use is obtained within two years of date of manufacture.

APPLICATION

Surface Preparation ... Follow surface preparation directions of sealer being applied.

Application Method ... SURE-STEP is designed to be incorporated into a suitable concrete sealer. Minimum addition ratio is 16 oz. (473 mL) per five-gallon (18.9 L) pail. Additional SURE-STEP can be added, depending on the desired texturing effect. Do not exceed eight oz. per gallon. Stir, while adding SURE-STEP to the container of sealer. The product may float at first, but once it has wet out, it will mix in easily. In thinner products, occasional stirring during application may be required to keep the particles well suspended within the coating. It is recommended that when mixing SURE-STEP into unfamiliar sealers that a small test batch is mixed, followed by a small test application.

Drying Time ... Follow directions of sealer being applied.

Cleanup ... Follow directions of sealer being applied.

PRECAUTIONS

SURE-STEP will increase the texturing effect of a sealer, but the addition of the slip-resistant additive should not be considered non-skid, anti-skid, or non-slip. Under some conditions, the granules may be visible. Depending on the surface, this may alter color or dull the surface. A small application test section is recommended.

CONTINUED ON REVERSE SIDE...

HEALTH HAZARDS

SURE-STEP is not hazardous and does not contain silica, but should be treated as a nuisance dust while incorporating it into its intended vehicle. Use with adequate ventilation. Use appropriate, properly fitted respirator protection filter apparatus and avoid breathing dust and particles. If dizziness, headache, or eye watering occur, get to fresh air; leave area immediately. In case of eye contact, flush with large amounts of water for at least 15 minutes. Seek medical attention if irritation persists. Do not take internally. If swallowed, seek medical attention immediately. Keep out of reach of children. Close container after each use. Use protective clothing to avoid contact with skin and eyes. Refer to Safety Data Sheet for complete health and safety information.

LEED INFORMATION

May help contribute to LEED credits:

- MRc9: Construction and Demolition Waste Management

For most recent data sheet, further LEED information, and SDS, visit www.wrmeadows.com.



LIMITED WARRANTY

W. R. MEADOWS, INC. warrants at the time and place we make shipment, our material will be of good quality and will conform with our published specifications in force on the date of acceptance of the order. Read complete warranty. Copy furnished upon request.

Disclaimer

The information contained herein is included for illustrative purposes only, and to the best of our knowledge, is accurate and reliable. W. R. MEADOWS, INC. cannot however under any circumstances make any guarantee of results or assume any obligation or liability in connection with the use of this information. As W. R. MEADOWS, INC. has no control over the use to which others may put its product, it is recommended that the products be tested to determine if suitable for specific application and/or our information is valid in a particular circumstance. Responsibility remains with the architect or engineer, contractor and owner for the design, application and proper installation of each product. Specifier and user shall determine the suitability of products for specific application and assume all responsibilities in connection therewith.